

GOES-19 ABI Fire Detection and Characterization Release
Provisional Data Quality
March 6, 2025
Read-Me for Data Users

The GOES-R Peer/Stakeholder Product Validation Review (PS-PVR) for GOES-19 Advanced Baseline Imager (ABI) L2+ Fire / Hot Spot Characterization (FHS) Provisional Maturity was held on March 5, 2025. As a result of this review, the panel chair declared that this product reached Provisional Maturity.

FHS consists of four product outputs: metadata mask, fire radiative power (FRP), instantaneous fire temperature, and instantaneous fire size. The metadata mask assigns a flag to every earth-navigated pixel that indicates its disposition with respect to the FHS algorithm. It includes six fire categories:

- Processed fire: The highest fire confidence category, includes FRP, size, and temperature estimates
- Saturated fire: Also very high confidence fires, but the pixel was at instrument saturation so no properties could be determined
- Cloudy fire: A high confidence fire that appears to be partially obscured by cloud
- High possibility fire: A likely fire that did not meet the thresholds for the Processed category
- Medium possibility fire: Medium confidence fire category
- Low possibility fire: The lowest confidence class, a large number of false alarms are to be expected, also contains small and/or cooler fires

Each of the fire categories has a temporally filtered equivalent, which is triggered if fire was found within +/-1 pixel in the last 12 hours. Also included in the mask are flags that indicate why a pixel was excluded from consideration, including due to water, certain surface types, clouds, and bad data.

The FRP, size, and temperature fields represent the properties of a fire that would produce the same detected radiant energy for the pixel. Fires vary throughout their burn area in intensity, but the satellite measurement is a composite signal of the entire pixel. FRP, size, and temperature represent the composite properties of that pixel. A hypothetical fire with those properties would produce the same measured radiances. Due to this mixing of subpixel elements and diffraction in the sensor there are large error bars on these retrievals.

The FHS products are generated for every ABI Full Disk (FD) of the Earth, Contiguous United States (CONUS) region, and Mesoscale (MESO) regions.

A full description and format of the FHS product can be found in the Product Definition and User's Guide (PUG) Volume 5 (<https://www.ospo.noaa.gov/resources/documents/goes-r.html>). The algorithm used to derive the FHS products from GOES-19 ABI observations is described in detail in the "GOES-R Advanced Baseline Imager (ABI) Algorithm Theoretical Basis Document for Fire / Hot Spot Characterization" (https://www.star.nesdis.noaa.gov/goesr/documentation_ATBDs.php).

Provisional maturity, by definition, means that:

- Validation activities are ongoing and the general research community is now encouraged to participate;
- Severe algorithm anomalies are identified and under analysis. Solutions to anomalies are in development and testing;
- Incremental product improvements may still be occurring;

- Product performance has been demonstrated through analysis of a small number of independent measurements obtained from select locations, periods, and associated ground truth or field campaign efforts;
- Product analysis is sufficient to communicate product performance to users relative to expectations (Performance Baseline);
- Documentation of product performance exists that includes recommended remediation strategies for all anomalies and weaknesses. Any algorithm changes associated with severe anomalies have been documented, implemented, tested, and shared with the user community;
- Testing has been fully documented; and
- Product is ready for operational use and for use in comprehensive calibration/validation activities and product optimization.

Provisional users bear all responsibility for inspecting the data prior to use and for the manner in which the data are utilized. Persons desiring to use the GOES-19 ABI Provisional Maturity Fire/Hot Spot Characterization product for any reason, including but not limited to scientific and technical investigations, are encouraged to consult the NOAA algorithm working group (AWG) scientists for feasibility of the planned applications. This product is sensitive to upstream processing, such as the quality of the calibration and navigation of input ABI L1b data. NOAA requests that any organizations that publicly share GOES-19 data -- before it is declared operational -- include the following disclaimer with the data: "GOES-19 Preliminary, Non-Operational Data".

Known issues at this stage include:

1. Missing values occur randomly due to upstream L1b issues, typically in the form of rectangular blocks.
2. False alarms are known to occur due to relatively solitary water clouds (i.e., surrounded by ice clouds or cloud free ground) causing reflections that appear fire-like, particularly at high solar zenith angles.
3. False alarms due to surface heterogeneity, such as bare ground surrounded by vegetated fields, power plant cooling lakes, urban areas that are not properly screened out, coastlines, and others, are known to occur and tend to recur in the same locations at certain times of year – these most frequently manifest as low possibility and processed fires.
4. Co-registration errors in the L1b data between bands 7 and 14 can lead to numerous false alarms, particularly during the daytime hours and often manifesting as false alarms that follow geographic features.
5. The temporal filtering is not functioning as designed and only considers the fire pixels of each scan mode separately, as a result those pixels should be treated the same as other fire pixels.
6. Detections and characterizations will differ between satellites, even when they contain the same instruments, due to viewing geometry, clouds in the line of sight, and surface topography.

Please report any systematic false alarms and other concerns to the AWG FHS science team.

Contact for further information: OSPO User Services at SPSD.UserServices@noaa.gov

Contacts for specific information on the ABI L2+ FHS product:

Chris Schmidt chris.schmidt@ssec.wisc.edu

Ivan Csiszar ivan.csiszar@noaa.gov